

160

VERSIONS

DK (with Diesel "Kubota" engine)
 GPL (with LPG engine "Kubota")
 E (electric-battery operated)

MAIN FEATURES

- Dashboard with bright indicators and hydraulic control device by levers
- Dust filter in polyester-textile with electric filter shaker
- Hydraulic height dump up for empty



Technical specifications	160DK	160GPL	160E
SWEEPING SYSTEM			
Cleaning path:			
- with main-brush only	100 cm	100 cm	100 cm
- with main-brush + right side brush	130 cm	130 cm	130 cm
- with main-brush + right and left side brush	160 cm	160 cm	160 cm
Theoretical max. coverage rate per hour	11.500 mq	11.500 mq	8.700 mq
Waste hopper capacity	300 l	300 l	300 l
Filtering surface textile polyester filter	7,8 mq	7,8 mq	7,8 mq
PROPELLING SYSTEM			
D.C. electric motor 36 V	.	.	4.560 W
Kubota engine 3 cyl.	16,5 Kw	17,5 Kw	
Battery (voltage/capacity)			36/360 V/A-h
DIMENSIONS AND WEIGHT			
Length	222 cm	222 cm	222 cm
Width	135 cm	135 cm	135 cm
Height	146 cm	146 cm	146 cm
Weight (empty) (*) without battery	1.399 kg	1.399 kg	850 (*) kg
ON REQUEST ACCESSORIES			

Technical specifications should be modified without notice